



## Karry Specifications

		1.6-MT	1.5-MT
	Powertrain		
	Model bulletin	SQR6468A1	SQR6462A187
<b>Emission</b>			
	EU III	●	
	EU IV + OBD		●
<b>Safety &amp; security</b>			
Airbag	Driver airbags		●
Seat belt	Front driver 3-point seat belts with pretensioners	●	●
	Rear 3-point seat belts with ELR (3 seat belts)	●	●
Brake	Front wheel ventilation discs brake	●	●
	Rear wheel drums brake	●	●
	Energy-absorbing steering column	●	●
	ABS+EBD		●
Foglight	Front foglamp	●	●
	High mounted brakelamp	●	●
<b>Technical</b>			
	Length (mm)		4610
	Width(mm)		1693
	Height(mm)		1855
	Wheelbase(mm)		2700
	Minimum turning radius(m)		5.45
	Curb weight / gross vehicle weight rating(kg)		1300
	The accelerate time for 0-100km/h (s)		23
	Max. speed (km/h)		141
	Engine Model	SQR480ED	SQR477F



Transmission model	AQ015AA	QR515MHE
Transmission-number of speeds and type	5MT	
Max. power (kw/rpm)	65/5500	80/6000
Max. torque (n.m/rpm)	132/3500	140/4500
Engine displacement	1596	1497
Cylinder diameter	79.96	77.4
Piston stroke	79.52	
The number of engine cylinder and arrange type	4 in line	
Compress ratio	9.75:1	10.5:1
The number of cylinder valve	4	
Value gear type (DOHC,SOHC)	DOHC	
The number of seat	7	5
The number of door	4	
Drive wheel	Front wheel	
Fuel type	Gasoline	
Fuel tank capacity (L)	65	
Wheel	185/70 R14 tyre	
Front suspension/stabilizer bar/spring type/independent suspension	Independent Macpherson strut with stabilizer, cylindrical coil spring and dual-acting tube damper.	
Rear suspension/stabilizer bar/spring type/independent suspension	Leaf spring rigid axle suspension with dual-acting tube damper and welded rear axle.	