



QQ3 Specifications

	Powertrain	0.8MT	1.1MT	1.1-AMT
	Model code	SQR7080	SQR7111S11	SQR7110S11T
Emission				
	EU II	●		●
	EU III		●	
Safety & security				
Airbag	Driver and front passenger airbags		●	
Seat belt	Front 3-point seat belts with ELR	●	●	●
	Rear outer 3-point seat belts with ELR	●	●	●
Brake	Front discs brake	●	●	●
	Rear drum brake	●	●	●
	Energy-absorbing steering column	●	●	●
	ABS+EBD		●	
Anti-theft	Body anti-theft		●	
	Four door jam alarm	●	●	●
Foglight	Single tone horn	●	●	●
	Front foglights	●	●	●
	Rear foglights	●	●	●
	High mounted brakelamp	●	●	●
Technical				
	Overall length (mm)		3550	
	Overall width (mm)		1495	
	Overall height (mm)		1485 (1530)	
	Wheelbase (mm)		2340	
	Turning radius (m)		5	



Weights - curb weight / gross vehicle weight rating (kg)	880/1255	890/1265	900/1275
The accelerate time for 0-100km/h (s)	30	20	18
Max. speed (km/h)	130		
Engine code	SQR372	SQR472F	
Gearbox code	QR512	QR512	QR512E
Transmission - number of speeds / type	5MT		
Maximum power (kw/rpm)	38/6000	50/6000	
Maximum torque (n.m/rpm)	70/3500~4000	90/3500~4000	
Engine - liters / (cc)	812	1083	
Engine bore (mm)	72		
Engine stroke (mm)	66.5		
Engine configuration - number of cylinders	3 in line	4 in line	
Engine compression ratio	9.5:1		
Number of valves per cylinder	4		
Engine valve gear type	DOHC		
Seating capacity	5		
Number of doors	5		
Driven wheels	Front		
Fuel - type / other fuel type	Gasoline		
Fuel tank capacity (L)	35		
Wheel	155/65 R13 tyre		
Front suspension - type / stabilizer bar / spring type / wheel dependence	Macpherson strut with cylindrical coil spring, dual-tube damper and single transverse link		
Rear suspension - type / stabilizer bar / spring type / wheel dependence	Rigid axle trailing arm type with cylindrical coil spring and dual-tube damper		